



- 4-vapour permeable collar
- 17-rafter
- 22-thermal insulation
- 109-air-tight flashing
- 147-EL FAKRO flashing upper element
- 148-EL FAKRO flashing side element
- 149-EL FAKRO flashing lower element
- 788-egress roof windows FWU FAKRO

**FWU G3/G31 - DIMENSIONS**

Window size[in]	Outside frame SxL				Rough opening WxR				Daylight Area (glass)	
	S [in]	S [mm]	L [in]	L [mm]	W [in]	W [mm]	R [in]	R [mm]	[Sq ft]	[m²]
24x38	23 1/2	596	38 3/8"	974	22 3/8	568	37 3/8	952	3,55	0,33
24x46	23 1/2	596	46 1/4	1174	22 3/8	568	45 3/8	1152	4,41	0,41
37x46*	36 7/8	937	46 1/4	1175	38 1/2	977	47 3/4	1215	10	0,93

\* Size available to order - install with mounting brackets

	FWU	ELW	SLATE	

Vertical and horizontal cross-section: EGRESS ROOF WINDOW FWU G3/G31 with ELW flashing for flat tiled roofs	FORMAT A4	SCALE 1:10/1:5	DATA 02.2024
---	--------------	-------------------	-----------------

Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality on the roof. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.