



- 4-ice and water guard by others
- 17-rafter
- 22-thermal insulation
- 57-Vertical joining gutter FAKRO
- 98-FX non-opening skylight
- 109-air-tight flashing
- 147-EL FAKRO flashing upper element
- 148-EL FAKRO flashing side element
- 149-EL FAKRO flashing lower element

FIXED SKYLIGHT FX

Window size[in] SxL	S [in]	S [mm]	L [in]	L [mm]	Rough opening			
					W [in]	W [mm]	R [in]	R [mm]
16x46	16 1/2	419	46 3/8	1178	14 1/2	364	45 1/2	1157
24x27	24 1/2	623	27 1/2	699	22 1/2	568	26 1/2	678
24x38	24 1/2	623	38 1/2	978	22 1/2	568	37 1/2	957
24x46	24 1/2	623	46 3/8	1178	22 1/2	568	45 1/2	1157
24x55	24 1/2	623	55	1397	22 1/2	568	54	1376
24x70	24 1/2	623	70 3/4	1797	22 1/2	568	70	1776
32x38	32 1/2	826	38 1/2	978	30 1/2	771	37 1/2	957
32x46	32 1/2	826	46 3/8	1178	30 1/2	771	45 1/2	1157
32x55	32 1/2	826	55	1397	30 1/2	771	54	1376
48x27	48 1/2	1232	27 1/2	699	46 1/2	1177	26 1/2	678
48x46	48 1/2	1232	46 3/8	1178	46 1/2	1177	45 1/2	1157



15° - 85°

Vertical and horizontal cross-sections:  
FX non-opening Skylight with flashing EL  
for flat tiled roofs, B2/1 combination

FORMAT:  
A4

SCALE:  
1:10/1:5

DATA:  
06.2022